Application No.: 10/615,868 Docket No.: 2450-0518P

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A burglar alarm light comprising a shell, a lamp set located in the shell, a shade coupled on a front end of the shell, and an adjustment mechanism located in the shell to adjust displacement of the lamp set, 5wherein the adjustment mechanism includes:

a seat having a bottom section which has an aperture formed thereon and two opposing ends extending upwards to form respectively a first extended section, the first extended section having an operation slot;

a moving member located in the seat having a bottom which has a hole and two opposing ends extended upwards to form respectively a first arm, the first arm having a guiding member; and

a rotary member running through the bottom section of the seat and the bottom of the moving member;

wherein the adjustment mechanism adjusts the displacement of the lamp set to alter projection type of light, including converging or scattering, emitted by a light source,

wherein the first extended section of the seat has a first lug on the periphery thereof and a second lug extending inwards.

2. (Cancelled)

3. (Original) The burglar alarm light of claim 1, wherein the first arm of the moving member has one end extended inwards to form a second arm.

3 KM/asc

Application No.: 10/615,868 Docket No.: 2450-0518P

4. (Original) The burglar alarm light of claim 3, wherein the second arm has an anchor hole.

- 5. (Original) The burglar alarm light of claim 1, wherein the rotary member has screw threads.
- 6. (Original) The burglar alarm light of claim 1, wherein the rotary member is selectively a screw or a worm.
- 7. (Original) The burglar alarm light of claim 1, wherein the adjustment mechanism has a first retaining member to confine the rotary member on the seat.
- 8. (Original) The burglar alarm light of claim 1, wherein the adjustment mechanism has an adjusting member coupled on the rotary member to drive and rotate the rotary member.
- 9. (Original) The burglar alarm light of claim 1, wherein the adjustment mechanism has an anchor member to anchor the adjustment member on the shell.
- 10. (Original) The burglar alarm light of claim 1, wherein the lamp set includes a socket, a spacer and a lamp bulb.

4 KM/asc

Application No.: 10/615,868 Docket No.: 2450-0518P

11. (Original) The burglar alarm light of claim 1, wherein the shade includes a reflective mirror.

5 KM/asc